

Refer to page 40  
for Wheel Brush  
Adapters.



21529

## Basic Sections - Crimped Silicon Carbide

Diam.	Filament Size/Grit	Approx. Face Width	Width at Faceplate	Trim Length	Arbor Hole	Max. RPM	Catalog Number	Std. Pack	Item Number	List Price Ea.
4-1/2	.022/320	17/32	17/32	3/4	2	6,000	AM45A	2	21519*	\$39.63
	.035/180								21509*	39.63
	.040/120								21499	39.63
6	.022/320	17/32	17/32	1-1/2	2	6,000	AM6A	2	21549	40.21
	.035/180								21539	40.21
	.040/120								21529	40.21
8	.022/320	17/32	17/32	1-7/8	3-1/4	5,000	AM8A	2	21570	69.46
	.035/180								21560	69.46
	.040/120								21550*	69.46
10	.022/320	17/32	17/32	2-7/8	3-1/4	4,500	AM10A	2	21600*	89.73
	.035/180								21590	89.73
	.040/120								21580	89.73
14	.022/320	17/32	9/16	3-7/8	5-1/4	3,000	AM14A	2	19810	152.91
	.035/180								21690	170.65
	.040/120								21680*	170.65

\* Non-returnable item. Call Customer Service for availability.

Note: Basic sections are designed to be ganged in sets with a minimum gap between sections or as single units with pressboard adapters and steel flanges.



21463

## Multi-Duty Wheels - Crimped Silicon Carbide

Diam.	Filament Size/Grit	Approx. Face Width	Width at Faceplate	Trim Length	Arbor Hole	Max. RPM	Catalog Number	Std. Pack	Item Number	List Price Ea.
3	.022/320	3/8	13/32	7/16	1/2-3/8	6,000	DM3A	5	21453*	\$23.02
	.035/180								21443	23.02
	.040/120								21433	23.02
	.040/120								22343*	23.02
4	.022/320	7/16	7/16	15/16	1/2-3/8	6,000	DM4A	5	21483	26.55
	.035/180								21473	26.55
	.040/120								21463	26.55
	.040/120								20364	57.66
6	.022/320	5/8	11/16	7/8	5/8-1/2	4,500	DMX6A	5	20354	57.66
	.035/180								20354	57.66
	.040/120								20344	57.66

\* Non-returnable item. Call Customer Service for availability.

★ Aluminum Oxide



10064

## Small Diameter Wheels - Crimped Silicon Carbide

Diam.	Filament Size/Grit	Approx. Face Width	Width at Faceplate	Trim Length	Arbor Hole	Max. RPM	Catalog Number	Std. Pack	Item Number	List Price Ea.
2	.022/320	1/4	9/32	9/16	1/2-3/8	10,000	SS20A	10	09983	\$11.85
	.035/180								09993	11.85
	.040/120								10003	11.85
2-1/2	.022/320	1/4	5/16	3/4	1/2-3/8	10,000	SS24A	10	10023	15.47
	.035/180								10033	15.87
	.040/80								10053	15.87
3	.022/320	1/4	5/16	15/16	5/8-1/2	10,000	SS30A	10	10064	17.48
	.035/180								10074	17.48
	.040/120								10084	17.48
	.040/80								10094	17.48

Refer to page 31  
for additional  
operating  
information.

## Wheel Brush Operating Speeds

The Maximum Safe Free Speed (RPM) for Anderlon Wheel Brushes is not the recommended operating speed. The RPM in some cases is almost double the optimum operating speed. For best results, these brushes should not be operated at speeds above 3,500 SFPM (Surface Feet Per Minute). Below are recommended starting speeds:

Diameter:	RPM:	Diameter:	RPM:
2	4,000 - 6,000	8	1,200 - 1,500
3	3,000 - 4,000	10	1,000 - 1,200
4	2,000 - 3,000	12	800 - 1,000
6	1,500 - 2,000	14	800 - 900