



03789

## Andermax™ High-Density Crimped Wire Wheels - DMXX Series

Large diameter wheels for specialized equipment used for rubber buffing, edge blending, gear deburring and flash removal.

Diam.	Wire Size	Arbor Hole	Trim Length	Face Width	Width at Faceplate	Max. RPM	Catalog Number	Standard Pack	Item No. Steel	List Price Ea.
12	.006	2*	1-5/8	1-1/8	3/4	3,000	DMXX12-7	1	04329*	\$177.15
	.0118								04349*	132.16
	.014								04359*	133.00
12	.006	2*	3/4	3/4	13/16	3,000	DMXX12-9	1	03789*	263.72
	.0118								03809*	197.78
14	.0118	1-1/4°	1-3/4	7/8	13/16	2,400	DMXX14-9	1	03968*	271.74
15	.0118	2*	2-1/4	1	13/16	2,400	DMXX15-9	1	03889*	290.17

\* Non-returnable item. Call Customer Service for availability.

\* 1/2 x 1/4 Double Keyway

\* 1/4 x 1/8 Double Keyway

Refer to page 28 for Adapters and Drive Arbors.



27073

## Tampico Wheel - SS Series

For delicate brushing and finishing.



Diam.	Arbor Hole	Trim Length	Face Width	Width at Faceplate	Max. RPM	Catalog Number	Standard Pack	Item No. Tampico	List Price Ea.
3	1/2-3/8	1	1/2	3/8	20,000	SS30TN	10	27073	\$8.45

Refer to page 28 for Adapters.



26769

## Tampico Wheels - QTAM & TAM Series

For delicate brushing and finishing.



Diam.	Arbor Hole	Trim Length	Face Width	Width at Faceplate	Max. RPM	Catalog Number	Standard Pack	Item No. Tampico	List Price Ea.
6	2	1-1/2	17/32	17/32	6,000	QTAM6N	5	26769	\$27.36
8	3-1/4	1-7/8	17/32	1/2	5,000	TAM8N	5	27310	27.28
10	3-1/4	2-27/32	17/32	1/2	4,500	TAM10N	2	27330	36.06
12	4-1/4	3-3/8	17/32	17/32	4,000	TAM12N	2	27350	40.24

Refer to page 28 for Adapters and Drive Arbors.



72016

## Nylon Wheels - SS Series

For delicate, scratch-free finishing.



Diam.	Fill Diam.	Arbor Hole	Trim Length	Face Width	Max. RPM	Catalog Number	Standard Pack	Item No. Nylon	List Price Ea.
1-1/2	.010	3/8	7/16	1/4	20,000	SS14Y	10	27078*	\$11.36
2	.010	1/2	1/2	3/8	20,000	SS20Y	10	72016*	12.58
3	.016	5/8	15/16	1/2	20,000	SS30Y	10	70423*	14.30

\* Non-returnable item. Call Customer Service for availability.